

PRO SERIES ROUND TOP CAR HAULER



Standard Features

Height

• 6'6" Interior Height

Frame

- 6x2 Tube Frame and Tongue
- 16" On-Center Tube Wall Studs
- 16" On-Center C-Channel Floor Crossmembers
- Triple-Tube Tongue
- 24" On-Center Tube Roof Bows
- 48" Beavertail (24" on 16' unit)

Hitch

- 7-Way Molded Plug
- 2-5/16" Coupler on 7K and 10K
- Adjustable 2-5/16" Coupler on 14K
- Safety Chains
- Zinc-Plated Setback Jack on 7K
- 7K Setback Jack on 10K & 14K

Axle

- *Torsion Axles
- All Wheel Brakes

Wheels/Tires

- Easy Lube Hubs
- Radial Tires on Aluminum Wheels (up to 14K)

Interior

- 3/8 Inch Plywood Wall Liner w/Aluminum H-Trim (Eliminates Stapled Lauan Trim)
- 3/4" Engineered Wood Flooring
- (4) 6K D-Rings
- Thermo-Sheath® Ceiling Liner (Above Roof Bows)

12 Volt Electrical

- (2) 12 Volt Wall Mounted LED Dome Light (380 Lumens) w/1 Wall Switch LED 6" Oval Tail Lights
- w/Rubber mounted ¾" Bullet Marker Lights (All Clear Lens)
- *Integrated Backup Lights

Exterior

- .030 Smooth Aluminum Exterior
- Screw-less Exterior
- Bright Front Corners
- Bright Rear Hoop
- 24" Stoneguard w/Top Trim
- .080 Aluminum Roof Cove w/Seamless Aluminum Roof
- 3" Bottom Trim
- Aluminum Fenders
- Rubberized Undercoating
- Polyethylene Vapor Barrier
- Flow-Through Scoop Vents

Door

- 48"x70" RV Side Door w/Aluminum Door Holder and Step Well
- 4100 lb. Rated Heavy-Duty Rear Ramp Door w/Wood Flap

Limited 3-Year Warranty

SPECIFICATIONS

		7K	10K	14K
Model #	18'	STRCH10218TA	STRCH10218TA-100	STRCH10218TA-140
	20'	STRCH10220TA	STRCH10220TA-100	STRCH10220TA-140
	24'	STRCH10224TA	STRCH10224TA-100	STRCH10224TA-140
	28'	STRCH10228TA	STRCH10228TA-100	STRCH10228TA-140
GVWR (lb.		7000	9900	14000
GAWR (lb.axle)		3500	5200	7000
Curb Weight	18'	3250	3450	4155
	20'	3425	3600	4330
	24'	3900	3900	4650
	28'	4375	4325	4975
Payload	18'	3750	6450	9845
	20'	3575	6300	9670
	24'	3100	6000	9350
	28'	2625	5575	9025
Frame		6x2, 1/8" Tube		6 x 2, 3/16" Tube
Cross Members		C-Channel (16" On-Center)		Tube (16" On-Center)
Tongue		6x2, 1/8" Tube		6 x 2, 3/16" Tube
/all Studs		Tube (16" On-Center)		
Roof Bows		Tube (24" On-Center)		Tube (16" On-Center)
Coupler		2 5/16" Ball		Adjustable 2-5/16" Ball
ack		2K Set-Back Jack 7K Dropleg		plea
enders		Aluminum Teardrop		P3
Easy Lube Axles		22.5 Degree Up Torsion		
Tires		205/75R 15 LRC	225/75R15 LRD	235/80R16 LRE
Wheels		15", 5 on 4.5, Radial	15". 6 on 5.5. Radial	16", 8 on 6.5, Radial
Wheels			Aluminum	, , , , , , , , , , , , , , , , , , , ,
Flooring		Engineered Wood		
ights		All LED Lights w/ Integrated Backup Lights		
ectric Plug		7 Pole RV Molded Flat Blade		
Exterior		.030 Aluminum		
Overall Length	18'	273"		
	20'	297"		
	24'	345"		
	28'	393"		
Overall Width			102"	
Overall Height		101"	101"	103"
Interior Height			81"	
Interior Width / Between Fenders		97" / 80.5"		
Interior Length	18'	225"		
	20'	249"		
	24'	297"		
	28'	345"		
Floor Height		21"	21"	23"
Rear Door Opening (WxH)		90" x 76.50"		
Ramp Door Capacity (lb.)			4100	

