





The FINN B40 Straw Blower brings mulching ease to small landscaping operations. You save time and energy by eliminating tedious and time consuming hand mulching. And because the unit is both self-powered and portable, it's easy for you to mulch in diverse locations.

Fast & Even Application.

The B40 Straw Blower provides you with mulch cover quality that's far superior to hand mulching. You're ensured of faster and more uniform growth. Blow mulch evenly over large areas with ease. The B40 Straw Blower efficiently shreds and blows 2-3 bales of straw in less than a minute.

Flexible & Effective Performance.

The B40 Straw Blower features a convenient discharge spout and optional 6" diameter, flexible hose. It's the ideal solution for proper mulching – providing soil moisture retention and protection against wind damage – in a wide variety of applications including the even cover of newly seeded lawns, around trees and shrubbery, berry beds, and bedding plants.

Specifically Designed To Meet Your Needs.

Like every piece of FINN equipment we produce, the B40 Straw Blower is the result of skilled and experienced manufacturing, as well as the valuable input received from our customers. We heard the call for a small and economical, yet highly

productive, straw blower; a compact unit with directional discharge and the ability to handle difficult material. The FINN B40 Straw Blower does it all!

As the world leader for over 70 years in the design and manufacture of innovative, quality equipment for the erosion control industry, FINN Corporation is committed to your complete satisfaction.



B40 Straw Blower Trailer Mounted (B40T)

 ${\it Model shown may include optional equipment.}$









Model B40 Straw Blower

B40 SKID MOUNT





FINN MODEL B40 TECHNICAL SPECIFICATIONS

POWER	. Kohler Command, 20 hp (14.9 kw), electric start	
ENGINE SAFETYSYSTEM	Low oil pr	essure shutoff
CAPACITY	2-3 bales	per minute
FUEL TANKCAPACITY	.5 gallon (ʻ	18.9 liter)
BLOWER	.17" (43 cm	n) diameter fan with 6 blades
RANGE	Up to 45 f	t. (13.7 m)
FEED	Manual	
DISCHARGE HEAD		balanced, 360 degrees horizontal rotation and s vertical travel
TRAILER OPTION	Independent suspension rubber torsion axle, 20.5x8x10 highway tread tires, fenders, D.O.T highway lights, safety rails, parking jack, 2" (5 cm) ball hitch. Includes electric brakes with break away switch	
FEED TRAY Horizontal, collapsible feed tray		
WEIGHT	B40S B40T	565 lbs. (256 kg) 1,165 lbs. (528 kg)

FINN Corporation has a policy of continuous product improvement, and reserves the right to change design and specifications without notice.

