



Parts & Service

Power Tools for **Professionals**



1" SDS-plus® BULLDOG Xtreme Rotary Hammer

11255VSR Plus RHA-50 Right Angle Attachment



Benefits: 11255VSR 1" SDS-plus® BULLDOG Xtreme Rotary Hammer

7.5 Amp; 0-1, 300 RPM; 0-5,800 BPM

HammerHook[™] allows quick tool storage during the job

Multi-function selector — 3 modes of operation, rotation only, rotary hammer and hammer-only mode

Vario-Lock™ positioning — rotates and locks chisel into 36 different positions to optimize working angle

Patented rotating brush plate — provides equal power in forward and reverse

Patented cord turret — 35° pivot for added flexibility and longer cord life

SDS-plus® bit system — tool-free bit changes with automatic bit locking, dust protection and maximum impact energy transfer rate

D-handle design — ideal for overhead and downward drilling applications

Variable-speed reversing trigger — for accurate bit starting as well as removing fasteners or bound bits Integral clutch — helps minimize torque reaction

Specifications: 11255VSR 1" SDS-plus® BULLDOG Xtreme Rotary Hammer

Amperage	7.5
Certifications	CSA
Cord Length	8 ft
Height	6"

Impact Energy/EPTA (ft. lbs.)	2.2
Length	17.25"
Max. Hole Diameter in Concrete	1"
Max. Hole Diameter in ConcreteThin Wa	2-5/8"
Max. Hole Diameter in Steel	1/2"
Max. Hole Diameter in Wood	3/4" - 1"
No Load BPM	0 - 5,800
No Load RPM	0-1,300
Optimal Concrete Capacity Range	3/16" - 5/8"
Rating	120V
Voltage	120V
Warranty	Limited 1 Year
Weight	6.7 lb

Includes

Auxiliary Handle -- 2 602 025 141 Depth Gauge -- 1 613 001 010 Carrying Case -- 2 610 994 810