



Click Here To View
Item at
www.GapPower.com

Sales • Rentals
Parts & Service



Speed Ex™

Cord-electric, Self-Contained Carpet Extractor specifications



Brush Drive System

| | |
|----------------------|-------------------------------------|
| Brush bristle length | 0.9 in / 22 mm |
| Brush bristle type | Nylon construction, Reverse chevron |
| Brush diameter | 3.5 in / 89 mm |
| Brush length | 15 in / 380 mm |
| Brush motor power | 0.4 hp / 0.3 kW |
| Brush motor voltage | 120 V / 230 V |
| Brush RPM | 1,200 rpm |
| Motor RPM | 2,400 rpm |

Chassis / Body Construction

| | |
|----------------------|---|
| Chassis construction | Cast aluminum frame, rotational molded tanks and injection molded plastic cover |
| Wheel descriptions | 8 in / 200mm |

Vacuum System

| | |
|---------------------|----------------------------------|
| Airflow at orifice | 99 cfm / 2.8 m ³ /min |
| Vacuum motor amps | 7.1 amps/ 3.6 amps |
| Vacuum motor power | 1.2 hp / .89 kW |
| Vacuum motor stages | 2 stage |
| Sealed waterlift | 86 in / 2,180mm |

Dimensions (Handle folded flat for storage)

| | |
|---------------|----------------|
| Length | 27 in / 690 mm |
| Machine Width | 19 in / 480 mm |
| Height | 28 in / 710 mm |
| Net weight | 102 lb / 46 kg |

Solution & Recovery System

| | |
|----------------------------|-----------------|
| Solution tank capacity | 5 gal / 19 L |
| Recovery tank wet capacity | 5 gal / 19 L |
| Spray jet count | 2-quick connect |

Power Consumption

| | |
|-----------------------------|-----------------------------------|
| Amps | 10.8 amps / 5.4 amps |
| Voltage | 120 V / 230 V |
| Watts | 1300 watts |
| Cord | 50 ft / 15 m |
| Electrical Safety Approvals | ETL Tested for UL & CSA Standards |

Pump System

| | |
|-------------------------|--------------------|
| Solution pump pressure | 65 psi / 4.48 bar |
| Solution pump amps | .7 amp / .35 amp |
| Solution pump flow rate | .7 gpm / 2.6 L/min |

Sound Level *

| | |
|--------------------------------|--------|
| Decibel ration @ operators ear | 69 dBA |
|--------------------------------|--------|

Warranty

3 years/2500 hrs on parts and labor.
10 years on rotationally-molded polyethylene tanks. No travel.
Please contact your Nobles representative for additional warranty details.

* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA