



Parts & Service



3900 Kelley Avenue, Cleveland, Ohio 44114 Tel: 216-431-2600 Fax: 216-431-2601 e-mail: Sales@AlliedCP.com website: http://www.AlliedCP.com

## **Rammer Compact Series Breakers**

**Rammer Compact Range** hammers are built to meet the growing demands of the rental market and to offer contractors the most up-to-date hammer technology. The most notable feature of the new in hammers is their massive trapezoidal tool that offers considerable benefits over traditional small tools. This non-breakable tool offers extremely long service life combined with superior productivity.

In addition to the low-maintenance, long-life characteristics, the **Compact Range** hammers are designed to match mini excavators, skid steer loaders and a wide range of other compact carriers.



The Rammer Compact Range hammers feature:

- Trapezoidal tool Non-breakable - saving money and downtime
- Composite tool bushing
  Never has to be greased increased tool and bushing life
- Innovative mounting bracket Two brackets in one - direct pin on and easily adaptable for quick couplers
- Constant blow energy

Guarantees all blows are at full power

Model		108	211	315	522
Impact Energy Class	ft. Ibs.	200	250	350	500
Recommended Carrier Weight	1000 Ibs.	1.8-4 (MX) 1.3-2.9(SS)	2.6-5.7 (MX) 1.8-4 (SS)	3.5-7.9 (MX) 2.4-5.5 (SS)	5.5-12.1(MX) 3.5-8.6 (SS)
Frequency Ranges	bpm	400-1900	400-1900	400-1900	400-1900
Hydraulic Flow Required Range	gpm	3.2-7.9	3.7-10.6	4.2-13.2	5.3-18.5
Hydraulic Pressure Range	psi	1450-2030	1450-2030	1450-2030	1600-2180
Tool Diameter	inch	4.09	4.69	5.16	5.91
Working Weight	lbs.	154-176	220-254	298-342	452-518

Updated: