



Sales Rentals

Sales Service

Parts & Service



# MATAWAY® OVERSEEDERS

# There's simply nothing like these ultraversatile machines on the market.

The Mataway Overseeder delivers seed straight to the curve-shaped discs, placing it directly into the soil slits for unmatched seed-to-soil contact. The seed flow rate is easily controlled right from the operator's station, and the flow stops automatically when the reel is raised for maximum control and precise operation.



## **SPECIFICATIONS**

### **POWER**

Engine Model	. 4-cycle Honda® GX390; recoil start;
	on/off switch; low-oil alert
Displacement	
Fuel Capacity	1.6 gal. (6.1 L)
Oil Capacity	1.16 qt (1.1 L)

UNIT
ClutchSpring-loaded belt tightener
Drive4L-section V-belt to front wheels by gear box and
sealed roller chain; triple 3V-section V-belts engine to reel
Lubrication Oil splash in gear case,
pressure grease fitting elsewhere
Cutting Depth Adjustable for any desired depth to 1.5 in. (38 mm)
Seeding Width
Tires: Front
Tires: Rear(2) 10.25 x 4.10-4, 2-ply pneumatic, sawtooth tread
Productivity: Single Pass
Productivity: Double Pass
Seeding Blade 10 8 point, high carbon, heat treated blades,
2 in (51mm) spacing

## **OPTIONAL VERTICAL SLICER/DETHATCHER REELS**

Flail Blade Type	1/8 in. (3 mm) at 1 in. (25 mm) spacing
Fixed Blade Type	. 1/32 in. (1 mm) at 1/2 in. (13 mm) spacing;
	1/32 in. (1 mm) at 1 in. (25 mm) spacing;
	1/16 in. (2 mm) at 1 in. (25 mm) spacing;
	1/16 in. (2 mm) at 1 1/2 in. (38 mm) spacing

### **DIMENSIONS**

Weight: Wet-Overseeder	453	lb	(205 kg) w/o reel
Width			35.5 in. (902 mm)
Length			50 in. (1,270 mm)
Height			. 44 in. (1,118 mm)

Specifications subject to change without notice.



The seed depth guide allows for seeding at variable rates and for different grass varieties and applications.



Durable cutting blades can be adjusted down to a depth of 11/2".



Adjust the engine throttle and set the cutting depth right from the operator's station.

# WWW.RYANTURF.COM