



Sales Rentals

Sales Service

Parts & Service





Built for Heavy Material & Continuous Work

Series 2000 Features:

- Lifts up to 1,000 lb (455 kg)
- 10, 15, 20 and 25 foot heights (3.2, 4.6, 6.1 and 7.5 m)
- No tools required
- No loose hardware
- Mast hold-down secures mast for safe transport


Pulley Guards

Load cable cannot come off.



Reversible Forks

Using plunger pins, forks remove and reverse easily for added height or to get flush with a ceiling. No loose pieces!



Inside-Mast Cable Feed

Loading Bar

Cable feeds inside mast. removing exposed cable from near the operator's face.

Sumner-built Winch

Highly reliable, single-speed winch uses idler roller to feed cable evenly on the drum to avoid cable flats. Handles are removable when not in use.

10" Rough **Terrain Wheels**

Makes loading a truck or van hassle free (optional on Series 2000 Lifts).

Fast Action Stabilizer Legs

Mounted on base top, stabilizer legs fold down with ease and lock in place. Optional on models 2010 & 2015.



Fits through doorways!

Lockable 5" Casters

SUMNER

Œ

Hard tread urethane wheels with Delrin® bearings.



MADE IN USA

| Part No. | Description | Max Height | | Lifting Capacity | | Lift Weight | | Shipping Weight | |
|----------|--------------------|------------|-------|------------------|-----|-------------|-------|-----------------|-------|
| | | Feet | Meter | lb | kg | lb | kg | lb | kg |
| 783700 | 2010 Material Lift | 10' 5" | 3.2 | 1,000 | 455 | 188 | 85.5 | 223 | 104.4 |
| 783701 | 2015 Material Lift | 15' 2" | 4.6 | 800 | 360 | 280 | 127.3 | 315 | 143.2 |
| 783702 | 2020 Material Lift | 19' 11" | 6.1 | 800 | 360 | 355 | 161.4 | 390 | 177.3 |
| 783703 | 2025 Material Lift | 24' 8" | 7.5 | 650 | 300 | 430 | 195.5 | 465 | 211.4 |










One piece slide-lock mechanism releases with plunger pins to fold legs. Leg rollers allow lift to be wheeled around with legs in stored position.



Pipe Cradle (#783705)

- Great for duct pipe or other HVAC applications.
- Slides over standard forks.

Boom Carriage (#783642)

- Ideal for installing pipe or other lifting applications.
- Attaches with four plunger pins
- ➡ 40" (100 cm) reach
- Five (5) hooking options
- Load capacity decreases the farther boom is extended, from 650 to 200 lb (300 to 90 kg).



Fork Extensions (#783691)

- Push-button operation
- Extend forks from 28" to 42" (71–106 cm)
- Longer forks decreases weight capacity to 200 lb (90 kg) (clearly displayed on the forks when extended).

| Part No. | Description | | | | |
|----------|---|--|--|--|--|
| 783882 | Safety brake - 2010 Safety brake - 2015 Safety brake - 2020 | | | | |
| 783883 | Safety brake - 2015 | | | | |
| 783884 | Safety brake - 2020 | | | | |
| 783885 | Safety brake - 2025 | | | | |

Safety Brake

Each mast and carriage can have a factory installed, gravity actuated safety brake which holds loads in place in the event the cable should go slack.

| Series 2000 Material Lift Dimensions | 2010 | | 2015 | | 2020 | | 2025 | |
|--------------------------------------|---------|---------|---------|---------|---------|---------|---------|---------|
| Height - stowed | 6' 4" | 1.93 m |
| Length - stowed | 34" | 0.86 m |
| Height - operating | 6' 4" | 1.93 m |
| Length - operating | 5' 2" | 1.57 m | 5' 2" | 1.57 m | 6' 1" | 1.84 m | 6' 1" | 1.84 m |
| Base width | 31-1/4" | 0.80 m |
| Width with stabilizer legs | 6' 2" | 1.88 m |
| Ground clearance | 2-1/2" | 6.4 cm |
| Load height (minimum) | 6" | 15.2 cm |
| Maximum height (forks down) | 8' 7" | 2.6 m | 13' 4" | 4.1 m | 18' 1" | 5.5 m | 22' 10" | 6.9 m |
| Maximum height (forks reversed) | 10' 5" | 3.2 m | 15' 2" | 4.6 m | 19' 11" | 6.1 m | 24' 8" | 7.5 m |



www.sumner.com

Sumner - U.S.

7514 Alabonson Road Houston, TX 77088 Ph: 281-999-6900 Fax: 281-999-6966

Sumner - Canada

470 Collier MacMillan Drive, Units 2 & 3 Cambridge, Ontario N1R 5Y7

Ph: 519-623-2300 Fax: 519-623-0744

Sumner - U.K.

Unit 16A, Blackpole Trading Estate East Blackpole Road Worcester WR3 8SG Ph: (44) 01905 458333 Fax: (44) 01905 458222

DISTRIBUTED BY: