



Sales Rentals

Sales Service

Parts & Service



JR. SOD CUTTER

SPECIFICATIONS

POWER

Honda [®]
Engine Model4-Cycle Honda GX160; recoil start;
on/off switch; low-oil alert
Displacement
Fuel Capacity

Briggs & Stratton®

Engine Model	4-Cycle Vanguard™; recoil start;
	dual-air cleaner; low-tone muffler
Displacement	
Fuel Capacity	0.87 gal. (3.3 L)
Oil Capacity	0.63 at (0.61)

UNIT

OIVII	
Clutch	Spring-loaded belt tightener
Drive	. V-belt engine to gear case; double roller chain to
blac	le eccentric shaft; gears and roller chain to traction
	wheels; transmission has separate dog clutches to
	engage cutting blade and traction drive
Drive Wheel	(2) 8 in. (203 mm) diameter, knob tread;
	rubber-vulcanized to cast-iron hubs
Lubrication	Oil splash in gear case
Speed	Up to 135 ft/min (41 m/min)
Cutting Width	12 in. (305 mm) or 18 in. (457 mm)
Cutting Thickness	Adjustable up to 2.5 in (64 mm)

DIMENSIONS

Weight/Wet: 12 in Model
Weight/Wet: 18 in Model
Width
Length
Height

Specifications subject to change without notice.

The Ryan® Jr. Sod Cutter has been the gold standard in the golf, rental and commercial industries for more than 50 years.

The improved Jr. Sod Cutter sports a host of new features, including reduced hand/arm vibration, cut by a remarkable 75 percent for more comfortable operation. A new pneumatic rear castor wheel with lockout allows curved landscape cutting with unmatched precision. A true workhorse, the Jr. Sod Cutter packs the speed, convenience and reliability you've come to expect from Ryan.





Semi-pneumatic swiveling rear wheel makes it easy to maneuver tightly around turns and cut closely along contoured landscape edges.



Rubber isolation mount absorbs much of the machine's vibration before it ever reaches your hands.



Easy depth and blade angle adjustment allow precise cutting in a wide variety of landscape contours and soil conditions.

WWW.RYANTURF.COM



ACCESSORIES

As if the Ryan® Jr. Sod Cutter isn't efficient and versatile enough, a full line of convenient accessories is available to make your job even easier – and more profitable. Each piece of equipment is easy to operate and simple to install. They're the ultimate compliment to an already industry-leading machine.



TOTE TRAILER

It takes just one person to load, unload and haul the Lawnaire® IV Plus, Lawnaire V Plus, or the Jr. Sod Cutter.



WIRE/TUBE PULLER

Easily bury wire or tubing up to 5" deep with minimal turf disturbance. The wire/tube puller is ideal for landscape lighting, irrigation systems and many other applications.



V-TRENCHER KIT

Install cable and perform other trenching tasks easily and inexpensively. Ideal for small to medium-sized trenching jobs.

OPTIONAL EQUIPMENT

Mole Blade 0.75 in. (19 mm) diameter kit;

1.25 in. (32 mm) diameter kit;

1 to 5 in. (25 to 127 mm) deep

Trench Blade. . . . V-shape trench to 6 in. (152 mm) deep

TOTE TRAILER SPECIFICATIONS

UNIT

Tires (2) 16.50×4.80 -8, 4-ply pneumatic tires on steel rims
with tapered roller bearings; fenders; tail lights with guards
Hitch Heavy-duty stamped steel housing,
fits 1 7/8 in. (48 mm) through 2 in. (51 mm) ball;
safety chain; drive wheel (2) 8 in. (203 mm) diameter,
knob tread; rubber-vulcanized to cast-iron hubs
Units Transported Jr. Sod Cutter, Lawnaire® IV Plus and
Lawnaire® V Plus aerators

DIMENSIONS

Weight			 											 		13	5 I	lb	(61	k	g)
Width			 									 		56	i	า. (1,	42	2 r	nn	n)
Length			 									 		 72	ii	า. (1,	82	9 r	nn	n)

Specifications subject to change without notice.