



Click Here To View
Item at

www.GapPower.com

*Sales • Rentals
Parts & Service*

Model E Series

ELECTRIC BOOM LIFTS



Features

- Eight 6V 370 Amp-Hour Deep Cycle Batteries
- Automatic Traction Control (ATC)
- Inward Self-Closing Swing Gate
- 180 Degree Hydraulic Platform Rotator
- 110V-AC Receptacle on Platform
- 5 Degree Tilt Alarm/Indicator Light
- Hourmeter
- Battery Condition Indicator
- Lifting/Tie Down Lugs
- Horn
- Operator Tool Tray
- All Motion Alarm

Accessories & Options

- Platform Worklights
- Mesh to Top Rail—Bolt-on Aluminum
- Acrylic Console Shield
- Cylinder Bellows
- UL® EE Rating¹
- Flashing Amber Beacon

1. Not available on Multi-Powered models

Please refer to the JLG Aerial Work Platform Sales Manual for additional features and accessories.

Specifications

Reach

Platform Height	
E300AJ/E 300AJP	30 ft (9.14 m)
E400A/E400AJP	40 ft (12.19 m)
E400A Narrow/E400AJP Narrow	40 ft (12.19 m)
E450A/E450AJ	45 ft (13.72 m)
Horizontal Outreach	
E/M400A Narrow	21 ft 2 in. (6.45 m)
E/M450A	23 ft 1 in. (7.04 m)
With Jib	
E300AJ	20 ft (6.1 m)
E/M450AJ	23 ft 9 in. (7.24 m)
With JibPLUS	
E300AJP	20 ft 6 in. (6.25 m)
E/M400AJP Narrow	22 ft 5 in. (6.83 m)
Up and Over Height	
E300AJ/E300AJP	13 ft 1 in. (3.99 m)
E400A/E400AJP	21 ft 6 in. (6.55 m)
E400A Narrow/E400AJP Narrow	21 ft 6 in. (6.55 m)
E450A	24 ft 7 in. (7.49 m)
E450AJ	25 ft 3 in. (7.7 m)
Swing	360 Degrees Non-Continuous
Platform Capacity	500 lb (227 kg)
Platform Rotator	180 Degrees Hydraulic
Jib (range of articulation)	
E300AJ/E300AJP	144 Degrees (+84, -60) Vertical
E400AJP/E400AJP Narrow	144 Degrees (+84, -60) Vertical
E450AJ	141 Degrees (+86, -55) Vertical
JibPLUS	
E300AJP/E400AJP/E400AJP Narrow	180 Degrees Horizontal

(continued on back page)



Versatility to Meet Your Needs

- Choose from three popular platform heights and three chassis widths
- Non-jib and optional jib models
- Automatic traction control for on and off slab mobility
- Zero emissions and low noise

Power to Stay On the Job Longer


- Industry-leading duty cycles
- Multi-power models provide round-the-clock operation and faster battery charging

Unmatched Reach and Positioning Capabilities


- Exclusive JibPLUS® boom option provides 180-degree range of side-to-side movement
- 48 in. narrow chassis models for narrow aisles
- Near vertical jib positioning and access to areas other machines can't reach
- Multiple function operation for efficient maneuvering in tight spaces

Specifications


E300



E400



E450



Dimensions

Platform Size	
E300AJ/E300AJ	30 x 48 in. (0.76 x 1.22 m)
E400A Narrow	30 x 48 in. (0.76 x 1.22 m)
E400AJ Narrow	30 x 48 in. (0.76 x 1.22 m)
E400A/E400AJ	30 x 60 in. (0.76 x 1.52 m)
E450A/E450AJ	30 x 60 in. (0.76 x 1.52 m)
Overall Width	
E300AJ/E300AJ	4 ft (1.22 m)
E400A/E400AJ/E450A/E450AJ	5 ft 9 in. (1.75 m)
E400A Narrow/E400AJ Narrow	4 ft 11 in. (1.5 m)
Tailswing	
E300AJ/E300AJ/E400A	Zero
E400AJ/E450A/E450AJ	Zero
E400A Narrow/E400AJ Narrow	4 in. (10 cm)
Stowed Height	
E300AJ/E300AJ/E400A	6 ft 7 in. (2.0 m)
E400AJ/E450AJ	6 ft 7 in. (2.0 m)
E400A Narrow/E400AJ Narrow	6 ft 5.75 in. (1.97 m)
E450A	6 ft 6 in. (1.98 m)
Stowed Length	
E400A/E400AJ/E400A Narrow	18 ft 1 in. (5.5 m)
E400AJ Narrow	18 ft 1 in. (5.5 m)
E450A	19 ft 1 in. (5.82 m)
With Jib	
E300AJ	18 ft (5.49 m)
E450AJ	21 ft 2 in. (6.45 m)
With JibPLUS	
E300AJ/E400AJ	18 ft 8 in. (5.70 m)
E400AJ Narrow	22 ft (6.7 m)
Wheelbase	
E300AJ/E300AJ	5 ft 5 in. (1.65 m)
E400A/E400AJ/E400A Narrow	6 ft 7 in. (2.0 m)
E400AJ Narrow/E450A/E450AJ	6 ft 7 in. (2.0 m)
Ground Clearance	
E300AJ/E300AJ	4 in. (10 cm)
E400A/E400AJ/E450A/E450AJ	8.5 in. (22 cm)
E400A Narrow/E400AJ Narrow	5 in. (13 cm)
Weight	
E400A/E400AJ	12,100 lb (5,488 kg)
E400A Narrow/E400AJ Narrow	13,100 lb (5,942 kg)
E450A	12,600 lb (5,715 kg)
With Jib	
E300AJ	15,400 lb (6,985 kg)
E450AJ	14,400 lb (6,532 kg)
With JibPLUS	
E300AJ	15,800 lb (7,166 kg)
E400AJ	13,700 lb (6,214 kg)
E400AJ Narrow	14,900 lb (6,759 kg)
Ground Bearing Pressure	
E300AJ/E300AJ	121 psi (8.47 kg/cm ²)
E400A/E400AJ	80 psi (5.6 kg/cm ²)
E400A Narrow/E400AJ Narrow	95 psi (6.7 kg/cm ²)
E450A	64 psi (4.48 kg/cm ²)
E450AJ	75 psi (5.25 kg/cm ²)
With JibPLUS	
E300AJ	130 psi (9.1 kg/cm ²)
E400AJ	74 psi (5.2 kg/cm ²)
E400AJ Narrow	185 psi (13.0 kg/cm ²)

Chassis

Drive Speed	
E300AJ/E300AJ	3.0 mph (4.8 kmph)
E400A Narrow/E400AJ Narrow	3.0 mph (4.8 kmph)
E400A/E400AJ/E450A/E450AJ	3.2 mph (5.2 kmph)
Gradeability	
E300AJ/E300AJ	25%
E400A/E400AJ/E400A Narrow	30%
E400AJ Narrow/E450A/E450AJ	30%
Turning Radius (Outside)	
E300AJ/E300AJ	5 ft (1.52 m)
E400A/E400AJ/E450A/E450AJ	2 ft (61 cm)
E400A Narrow/E400AJ Narrow	2 ft 10 in. (86 cm)
Turning Radius (Inside)	
E300AJ/E300AJ	10 ft 2 in. (3.1 m)
E400A/E400AJ/E400A Narrow	10 ft 4 in. (3.15 m)
E400AJ Narrow/E450A/E450AJ	10 ft 4 in. (3.15 m)
Tire Size/Type	
E300AJ/E300AJ	7.5 x 12 Non-Marking
E400A/E400AJ	240/55-17.5 pneumatic
E450A/E450AJ	240/55-17.5 pneumatic
Tire Size/Type (front)	
E400A Narrow/E400AJ Narrow	22 x 6 x 17.5 Non-Marking
Tire Size/Type (back)	
E400A Narrow/E400AJ Narrow	22 x 7 x 12 Non-Marking

Power Source

Electrical System	48V DC
Batteries	8 x 6V, 370 amp-hr
Drive Motors	Dual Electric Traction
Brakes	Automatic Spring Applied Multiple Disks
Hydraulic Motor/Pump	Permanent Magnet Motor/Gear Pump
Hydraulic Reservoir	
E300AJ/E300AJ	3 gal. (11.4 L)
E400A/E400AJ/E400A Narrow	4 gal. (15.2 L)
E400AJ Narrow/E450A/E450AJ	4 gal. (15.2 L)
Generator Set (Multi-Power Options)	
E400A/E400AJ/E400A Narrow	Fully Automatic, 45 Amp Kubota 6 hp Air-Cooled Engine
E400AJ Narrow/E450A/E450AJ	Fully Automatic, 45 Amp Kubota 6 hp Air-Cooled Engine
Engine Fuel Tank	
E400A/E400AJ/E400A Narrow	4 gal. (15.2 L)
E400AJ Narrow/E450A/E450AJ	4 gal. (15.2 L)



JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417

www.jlg.com

An Oshkosh Corporation Company