# **Troughing-Slider**

# **Conveyor**

# **Models**

The E-Z LIFT Troughing-Slider Conveyor is a medium duty conveyor designed to move loose and packaged materials at inclines up to 30 degrees. The conveyor's unique combination slider/roller bed makes it E-Z LIFTS's most versitile belt conveyor. Reversible, this conveyor can quickly move materials in and out!

### Typical uses include:

Dirt, gravel, sand, aggregates, grain, powders, cement, coal, and sludges. Cartons, shingles, firewood, rolls, and more!



### Features include:

- Heavy duty 2 ply rubber covered belt with 2" high cleats on 48" centers
- Combination slider/roller bed
- 7/8" O.D. high strength steel tubing truss frame 1-1/4" O.D. on 36 ft. model and 24" wide belts
- Approximate 120 FPM belt speed
- · Conveyor belt take-up adjustments
- · Self cleaning drive and idler belt pulleys
- Drive mounted at side of discharge end
- For electric motor direct drive speed reducer
- For gas engine internal V-belt and roller chain reduction and safety guards
- Operating, maintenance, and safety instructions

#### **Accessories:**

- · Electric motor or gas engine
- Start/Stop switch for electric motor
- Hopper
- Fork pockets
- Dolly and hitch assembly
- Tail-light assembly
- Towable elevating carriage

#### Options:

- Smooth belt
- Belt wiper
- Mini-cleated belt
- Forward/Stop/Reverse switch for electric motor
- Corrosion resistant PVC idler rollers



<b>Belt</b> –14" wide		
Model	Length	Approx. Wgt:
68-14	12 ft.	250 lbs.
70-14	16 ft.	300 lbs.
71-14	21 ft.	350 lbs.
73-14	26 ft.	400 lbs.
75-14	31 ft.	445 lbs.
77-14	36 ft.	515 lbs.

<b>CAPACITIES</b> – at 30° incline	
Lbs./Cu. Ft.	Tons/Hr.
30	22
50	36
75	54

	30 II.	o io ids.
CAPACITIES – at 30° incline		
s./Cu. Ft.		Tons/Hr.
30		22
50		36

## Multilift, Inc.

2000 South Cherokee, Denver, Colorado 80223 Denver Area: 303.733.5533 FAX 303.733.5642 North American Toll Free: 1.800.821.9966

Belt–18" wide		
Model	Length	Approx. Wgt:
68-18	12 ft.	265 lbs.
70-18	16 ft.	320 lbs.
71-18	21 ft.	375 lbs.
73-18	26 ft.	430 lbs.
75-18	31 ft.	490 lbs.
77-18	36 ft.	570 lbs.

<b>CAPACITIES</b> – at 30° incline	
Lbs./Cu. Ft.	Tons/Hr.
30	27
50	45
75	67

<b>Belt</b> –24" wide		
Model	Length	Approx. Wgt*
68-24	12 ft.	273 lbs.
70-24	16 ft.	343 lbs.
71-24	21 ft.	413 lbs.
73-24	26 ft.	475 lbs.
75-24	31 ft.	565 lbs.
77-24	36 ft.	670 lbs.

<b>CAPACITIES</b> – at 30° incline	
Lbs./Cu. Ft.	Tons/Hr.
30	36
50	60
75	90

E-mail: ez@ezliftconveyors.com Website: www.ezliftconveyors.com