## A 5KIBO COMPANY ®



## **Skidsteer Trailers**

The Pequea SST series skidsteer trailers are the choice trailer for the equipment professional. We made the frame extra heavy on all of our skidsteer trailers so an axle upgrade to 12,000 or 14,000 GVWR is possible. The strong diamond plate fenders are offset to allow 81" of clearance for those extra wide tracks. Standard 4" drop axles furnish one of the lowest loading angles around. No wonder this is the pro's choice.



Skidsteer Trailer	S					
Specifications	MP-16	MP-18	1014SST	1016SST	1018SST	1020SST
Overall Length	22'		20' 4"	22' 4"	24' 4"	26' 2"
Overall Width	99"		102"			
Deck Length	16'	18'	14'	16'	18'	20'
Deck Width	78 1/2"		81"			
Deck Height	23"		20"			
Hitch Height	19"-23"		16"-20"			
Mainframe	5" channel@6.7 lbs.		6" channel@10.5 lbs.			
Cross-Members	3" channel@4.1 lbs.		4" channel@5.4 lbs.			
Hitch	2 5/16" adj. ball or pintle					
Axles	(2) 6,000 II	bs. EZ lube	(2) 6,000 lbs. 4" drop EZ lube			
Brakes	Standard electric brakes (both axles)					
Suspension	Slipper leaf springs					
Wheel Size	6 bolt 15" silver mod.					
Tires	225/75D-15 LR "D" 2,540 lbs. load cap.					
Jack Capacity	5,000 lbs. drop leg		7,000 lbs. drop leg			
GVWR	10,000 lbs.					
Trailer Weight	2,000 lbs.	2,200 lbs.	2,200 lbs.	2,400 lbs.	2,600 lbs.	2,800 lbs.

Pequea reserves the right to change specifications, design and price of products described in this literature without notice. © 2010 Pequea.