



Sales Rentals

Sales Service

Parts & Service



## Tanaka TLE-600 Walk-behind Edger

The Tanaka TLE-600 cuts through overgrown edges faster than any belt driven walk-behind edger, stick edger, or shovel! For over 20 years, the world's FIRST-AND-ONLY shaft/gear driven walk-behind edger has been recognized as the number one machine for re-establishing overgrown sidewalk edges.

- 50 cc, 2.5 h.p. Tanaka two-stroke engine
- ☐ Solid steel drive shaft
- ☐ Heavy-duty, two-stage air filtration system
- Unique height adjustment system
- □ Two-year commercial use warranty / Seven-year consumer use warranty / One-year rental use warranty
- ☐ 54 lbs. (24.5 kg)

|             | SPECIFIC  | ATIONS   |   | Back-to-top                               |
|-------------|---|--|---|---|
|             |   | e Type:  | Tanaka two-stroke   | 2.7.5.62.22.2                             |
|             | Displacement CC (CU, IN.):<br>Output H.P.:<br>Fuel Tank Capacity FL. OZ. (C   |  | 50<br>2.5   |   |
|             |   |  |   |   |
|             | Cylina  | The second secon | Chrome Plated, Stress   | Relieved                                  |
|             | Connecting Rod:<br>Carburetion:<br>Starting System:<br>Ignition System:   |  | Forged Steel  |   |
|             |   |  | Walbro® Diaphragm<br>Standard Recoil<br>Transistorized Electronic |   |
|             |   |  |   |   |
|             |   | h System:  | Heavy-duty Centrifugal  |   |
|             | DRIV  | E SYSTEM   |   |   |
|             | Drive Shaft: Shaft Length IN. (MM): Drive Shaft End: Throttle Lock: Gear Ratio:   |  | 10.5 mm solid steel<br>8.3 (160)<br>Square<br>Yes<br>1.92 : 1     |   |
|             |   |  |   |   |
|             |   |  |   |   |
|             |   |  |   |   |
|             | Gear  | Ratio.   | 1.92 : 1  |   |
|             | BLAD  | E RELATED  |   |   |
|             |   | Length IN. (mm):   | 10 (254) 1/2 inch arbor   |   |
|             | Blade   | Material:  | Hardened Steel  |   |
| CUTTING ATT |   | ING ATTACHMENT   |   |   |
|             | Whee  | elt:   | Rear - 8" Rubber / Fron   | t - 8" Rubber (rounded edge)              |
|             | Cutting Depth:  | 3"   |   |   |
|             | MISC.   |  |   |   |
|             | Dry Weight / LBS. (KG):   | 54 (24.5)  |   |   |
|             | Shipping Weight / LBS. (KG<br>EPA Phase 2 Compliant:  | 6): 60 (27.2) (One carton)<br>Yes  |   |   |
|             | C.A.R.B. Tier II Compliant:   | No   |   |   |
|             | Gas / Oil Ratio:<br>Noise Level:  | 50:1<br>93 dbA   |   |   |
|             | Warranty:<br>Packaging:   | Two-year commercial use of One carton (Not Assemble  |   | e warranty / One-year rental use warranty |
|             |   |  |   |   |
| FE          | EATURES   |  | Back-to-top   |   |
|             | □ SOLID STEEL DRIVE SHAFT Provides maximum power to the cutting blade. □ UNIQUE HEIGHT ADJUSTMENT SYSTEM  |  |   |   |
|             |   |  |   |   |
|             |   |  |   |   |
|             | Allows you to easily set the blade height in one of nine different positions.   |  |   |   |
|             | □ HEAVY-DUTY, TWO STAGE AIR FILTRATION SYSTEM   |  |   |   |
|             | Provides maximum  | engine protection.   |   |   |
| ΔΙ          | DVANTAGES   |  | Back-to-top   |   |
|             |   |  | back to top   |   |
|             | <ul> <li>SOLID STEEL DRIVE SHAFT Provides more reliability than belt-driven models which are prone to stretc slip, or break.</li> <li>WEIGHS SIGNIFICANTLY LESS Than models that use bulky 4-cycle engine, reducing fatigue and makin transporting easier.</li> <li>MORE TORQUE Allows you to cut through overgrown edges faster and easier than belt-driven models.</li> </ul> |  |   |   |
|             |   |  |   |   |
|             |   |  |   |   |
|             |   |  | _   |   |

OFFSET BLADE Allows the rear wheel to remain flat when edging overgrown grass.